

CLASSIC DIESEL SERIES

DIIOOOT

GreenPower series genserating sets, 3000 rpm, equipped with KOHLER diesel engines with electric starting system with key and battery. These generating sets are characterized by lower consumption and a longer life expectancy compared to the petrol powered range. 3000 rpm gensets have been designed for stand-by use only. Not recommended using for more than 6 hours continuously or more than 500 hours/year.



The image is only for demonstration purposes

PRIME POWER	STAND-BY POWER	
kVA kW	kVA	kW
11 8,8	12,1	9,7



All data can be found out in the original technical datasheet of the engine and the alternator. Values shown are nominal values, they can change in every moment and without warning.



TECHNICAL DETAILS

	Electrical system type	3F+N	~
	Power factor	0,8	φ
	Voltage	400	V
	Frequency	50	Hz
	Ampere rating	15,9	A
ENGINE DATA	Engine	KOHLER KD425	
	Engine emissions standards	STAGE V	
	Engine power	14,2 (10,5)	Hp (kW)
	Rpm	3000	
	Nr. of cylinders	2	
	Engine starting system	Electric starter	
	Displacement	851	сс
FUEL CONSUMPION DATA	Fuel type	Diesel	
	Consumption	2,8	lt/h @ 75%
	Tank capacity	4	lt
	Autonomy	1,4	h
ALTERNATOR DATA	Alternator	LINZ ELECTRIC – NSM	MADE IN ITALY
	Туре	Self-excited, with brushes	
	Voltage regulation	AVR	
	Voltage precision	± 4	%



STANDARD EQUIPMENT



Steel base frame, epoxy powder painted



Anti-vibration dampers



First filling liquids



Electric starting with 12V battery



Electric manual panel: -n.1 230V EEC 16A 3P socket and n.1 400V EEC 16A 5P socket -General MCB, thermal switch, voltmeter and hour meter



OPTIONS



Slow trolley for manual handling

Automatic voltage regulator (AVR)



Bigger fuel tank for greater autonomy



Automatic mains failure panel -With integrated automatic transfer switch and battery charger

Greenpower AB

Helsingborgsvägen Varalöv, 262 96 Ängelholm, Sweden Phone: +46 43122240 Email: info@greenpower.se Web: www.greenpower.se