

TECHNICAL DATA SHEET

GP33 TR/S

STRUCTURE



Gear Box/alternator monoblock unit coupled through shaft, installed on a welded, powder-painted carbon steel base frame with demountable legs. (images are for illustrative purpose only)

ELECTRIC PANEL	
Magnetothermic circuit breaker	
Earth fault device	
63A 400V Socket	
16A 230V Socket	
E31 digital module:	
-	Voltmeter
-	Frequency meter
-	Hour counter

TECHNICAL DATA

EQUIPMENT SPECIFICATION (ISO 8528/1)		50Hz
Prime power at cosφ 0.8		30 kVA
Prime power at cosφ 0.8		24 kW
Voltage available to the terminals		400/230 V
Dimensions (mm)		855x580x985
Weight (Kg)		217

GEAR BOX		50Hz
Brand and model		6015.361.035
R.P.M.		1500

ALTERNATOR		50Hz
Brand and model		MECC ALTE ECP28-VL/4 (*)
Synchronous with electronic governor voltage		± 1%
Pole		4
Stator/rotator insulation		H
Protection level		IP23
Continuous power		30 kVA

(*) = or similar brand



Greenpower AB
Helsingborgsvägen Varalöv
262 96 Ängelholm
Tel: 0431 222 40
E mail: info@greenpower.se
web:www.greenpower.se